



Standard Specification	Unit	T-500B	T-500C	T-500-S	T-700B
X / Y / Z axis stroke	mm	500 x 400 x 460 (21T)/450 (26T)	500 x 400 x 320 (21T) / 310 (26T)	520 x 340 x 350 (21T) /340 (26T)	700 x 400 x 340 (21T) / 330 (26T)
Table size	mm	620 x 400	620 x 400	650 x 1000 (Double Side)	800 x 400
Max. load on table	kg	250	250	200 (Single Side)	250
Spindle speed	rpm	20-20000 (24000)	20-20000 (24000)	20- 20000 (24000)	20- 20000 (24000)
System		Fanuc / Mitsubishi / Siemens	Fanuc / Mitsubishi / Siemens	Fanuc / Mitsubishi / Siemens	Fanuc / Mitsubishi / Siemens
T Slot dimension	mm	3-14 x 120	3-14 x 120	3-14 x 100	3-18 x 125
Spindle motor power	kw	3.5 / 5.5	7.5 / 11	3.5 / 5.5	3.5 / 5.5
Spindle torque	nm	14.1 / 21	8.0 / 11.7	14.1 / 21	14.1 / 21
Auto tool changer (Magazine)		21 (26)	21 (26)	21 (26)	21 (26)
Max tool length / weight	mm / kg	200 / 3	200 / 3	200 / 3	200 / 3
Spindle taper		BT30	BT30	BT30	BT30
Rapid feed rate X/Y/Z	m/min	48 / 48 / 48	48 / 48 / 48	36 / 36 / 48	48 / 48 / 48
Power supply	kva	12	12	15	12
Width x Depth x Height	mm	1650 x 2450 x 2500	1700 x 2400 x 2300	3200 x 2090 x 2620	2100 x 2450x 2400
Weight	kg	3100	3050	5200	3150