



Item		Unit	DH-63	T-H11	T-H13	H-100
Axis travel	X/Y/Z axis travel	mm	1050/800/1000	1100/600/650	1350 /850 /750	2000 x 1300 x 1200
	Distance from spindle end to worktable center	mm	150-1150	175-825	90-840	350-1550
	Distance from spindle center to worktable top surface	mm	120-920	50-650	50-900	150-1450
	Max workpiece size	mm	1000×1000	1200 x 720	1450 x 950	2000 x 1300
Worktable	Worktable size	mm	630× 630 (2 pieces)	500 x 500	630 x630	1000 x 1250
	Worktable load	kg	1200×2=2400	500	1200	5000
	Minimum setting unit	deg °	0.001	0.001	1	0.001
Spindle	Motor power (rated/maximum)	kw	28/42	7.5 / 11	15/18.5	26/37
	Torque (rated/maximum)	nm	334/630	35.8 /95.5	143 /191	305 /512
	Maximum speed	r/min	10000	50-12000	50-6000	80-8000 /80-10000
	Taper	-	BT50	BT40	BT50	BT50
Tool magazine	Tool magazine capacity	t	50/60/100	24	24	24
	Tool length	mm	500	320	400	500
Speed	Cutting feed speed range	mm/min	1-15000	0-8000	0-10000	0-10000
	X,Y,Z rapid traverse rate	m/min	48/48/48	36 /36/36	20/20/20	24/24/24
System			Fanuc	Fanuc	Fanuc	Fanuc
Power		kw		25	40	85
Width x Depth x Height		mm		3400 x 3000 x 3000	4242 x 3008 x 3340	6880 x 4765 x 3560
Weight		kg		6800	11000	19000